



**Proudly Australian Built**



## Technical Features

- \* Turning capacity 15,000kg max. with min of 2 idler sets
- \* Pipe/Vessel diameter range 0.3 - 2 metre (depending on frame used)
- \* Variable speed range 100 – 600mm.per minute surface speed
- \* Inverter control, with in-built safety features.
- \* All welded construction.
- \* Solid natural rubber wheels, 525 x 300mm main drive. 525 x 150mm idler set.
- \* Precision aligned frame for No creep on rotation.
- \* Quality hand pendant with safety cut off fitted as standard
- \* Ample lifting eyes and folk lifting slots provided.
- \*\* 4 ton Idler SW-4TRI-2-2000-D525 single wheel set.
- \* Electrical compliance to AS/NZS 3000-2009

**Check total load capacity when choosing the number of**

**Smithweld Enterprises Pty Ltd**

227 Bank Street  
Welshpool WA 6106

Tel: 61 8 9470 6670

Email: sales@smithweld.com

# Product Information

SMITHWELD ENTERPRISES PTY LTD

## **PIPE/VESSEL ROTATOR 15,000kg Capacity**

### **Model SW-15TR-300-2000-D525**



## Specifications

Capacity:	15,000kg max.
Voltage:	240V/1ph/50Hz.
Speed range:	100 – 600mm
Overload protection:	current limiting protection.

## External Dimensions

Main frame length:	1.80 – 3.0 meter
Width:	860mm.
Height:	630mm.

Net Weight: 550kg main drive



**Optional**  
Foot control  
Model SW-10F  
with 10 metres of  
rubber cable.

