



Proudly Australian Built



Technical Features

- * Turning capacity at face plate 2000kg central load
- * Tilt capacity at face plate 2000kg max
- * Variable speed range 0 – 2 rpm on rotation
- * Quality digital controllers with safety shut-down and overload protection
- * Height adjustment of plate centre 600 – 900mm for 3rd Axis (Manual)
- * Quality hand pendant with 5m of shielded cable
- * Hold down 4 jaw chuck (optional) SW-800C
- * Built-In rotary 500amp. welding earth with bearing support
- * Face plate diameter 800mm

Safety

Rotation gear is fully covered to keep grinding dust out and to prevent accidental catching of cloths or fingers

Test data for tilt

800kg load @ 1200mm from plate
2000kg max load @ face plate

- * **Electrical compliance to AS/NZS 3000-2009**

Smithweld Enterprises Pty Ltd

227 Bank Street
Welshpool WA 6106

Tel: 61 8 9470 6670

Email: sales@smithweld.com

Product Information

SMITHWELD ENTERPRISES PTY LTD

PIPE POSITIONER **2000kg Capacity** **Model SW-2TP-2-2**



Specifications

Capacity on rotation:	2000kg
Voltage:	220-240v single phase

Industrial pendant:	on/off, tilt, speed control plus safety cut-out
---------------------	-------------------------------------------------

External Dimensions

Length:	1500mm
Width:	850mm
Height:	1250mm
Net Weight:	650kg

Shipping size: 1500L x 800W x 1000H



Optional extra
Foot control
Model SW-10F
With 10 metres of rubber cable

