



**Proudly Australian Built**



## Technical Features

- \* Fully sealed unit, protecting Motor/gearbox and electrical system
- \* Turning capacity 4000kg (max), when used with min of one idler
- \* Pipe diameter range 75 – 1200mm
- \* Wheel centres 280,430 & 560mm
- \* Variable speed range .01 – 3rpm
- \* Quality hand pendant supplied as standard
- \* All Welded Construction
- \* Solid 250mm rubber wheels
- \* Precision aligned frame for No creep on rotation
- \* Recessed controls
- \* Idler Pt. No. SW-1.5TRI-2 is required with main drive unit when turning 4000kg max load (Idler weight 61kg)
- \*\* Additional Idlers Recommended for pipe over 4 metres Long, depending on weight

**Smithweld Enterprises Pty Ltd**

227 Bank Street  
Welshpool WA 6106

Tel: 61 8 9470 6670

# Product Information

SMITHWELD ENTERPRISES PTY LTD

## **PIPE ROTATOR 4000kg Capacity**

### **Model SW-4TR-4-75-1200**



## Specifications

Capacity:	4000kg
Voltage:	220-240V single phase
Speed range:	0 – 3rpm
Overload protection:	current limiting Digital control

### Optional

Foot control  
Model SW-10F  
With 10 metres  
of rubber cable

## External Dimensions

Depth:	950mm
Width:	800mm
Height:	340mm

Net Weight:	138kg
Shipping Box (mm)	950D x 800W x 440H

Email: sales@smithweld.com

