



**Proudly Australian Built**



## Technical features

- \* Turning capacity 6000kg  
No of idlers will depend on wall thickness/diameter
- \* Pipe/vessel diameter range  
300 – 2000mm
- \* Variable wheel centres
- \* Variable speed range  
.01 – 2rpm
- \* Quality hand pendant with  
safety cut off fitted as  
standard
- \* All Welded Construction
- \* 400mm diameter solid  
rubber wheels
- \* Wheel width 150mm
- \* Precision aligned frame for  
No creep on rotation
- \* Recessed controls
- \* Optional foot switch SW-10F
- \* Optional idler Pt No SW-3TRI-2  
6000kg when used with main  
drive unit

# Product Information

SMITHWELD ENTERPRISES PTY LTD

## **PIPE ROTATOR 6000kg Capacity**

### Model SW-6TR-2-300-2000



### Specifications

Capacity max	6000kg
Voltage:	220-240V single phase
Speed range:	0 – 3rpm
Overload protection:	current limiting via Digital control

**Idler**  
Model  
SW-3TRI-2-300-2000

### External Dimensions

Length:	2500mm
Width:	550mm
Height:	340mm
 Net Weight:	 180kg



**Optional**  
Foot control  
Model SW-10F  
With 10 metres  
of rubber cable

**Smithweld Enterprises  
Pty Ltd**

227 Bank Street  
Welshpool WA 6106

Tel: 61 8 9470 6670

Email: sales@smithweld.com

