



Proudly Australian Built



Technical Features

- * Fully sealed unit, protecting Motor/gearbox and electrical system
- * Load capacity 4000 Kg
- * Cylinder diameter range 1500 mm
- * Variable speed range .01 – 3rpm
- * Recessed controls & digital speed readout for precise control of rotation speed.
- * Quality hand pendant with 10m of EM shielded cable & military spec plug supplied as standard
- * Precision aligned, all welded frame
- * **Optional** Heavy duty four jaw alignment & clamping chuck

Electrical compliance to AS/NZS 3000-2009

Smithweld Enterprises Pty Ltd

227 Bank Street
Welshpool WA 6106

Tel: 61 8 9470 6670

Email: sales@smithweld.com

Product Information

SMITHWELD ENTERPRISES PTY LTD

FLAT CYLINDER ROTATOR 4000 Kg Capacity

Model SW-4TFR-1500



Standard
Hand pendant
(SW-XTR-LT10)
with 10m of EM
shielded cable



Optional
H-duty foot control
(SW-10F)
With 10 metres of
rubber cable

Specifications

Capacity:	4000 Kg
Voltage:	220-240 VAC 1 ph
Speed range:	0 – 3 rpm
Overload protection:	Current (A) Voltage (V) Torque (Nm)

External Dimensions

Depth:	700 mm
Width:	1500 mm
Height:	340 mm

Net Weight: 138 Kg



© 2014